






PES beskonačne priveznice tip IRS



- vlačna čvrstoća: 650-800 N/mm²
- istezanje pri prekidu: cca. 12%
- upijanje vlage: 0,4 %
- talište: 260 °C
- maks. radna temperatura: do 100 °C
- dobra otpornost na kiseline
- srednje otporan na lužine
- dobra otpornost na organska otapala
- dobra otpornost na oksidirajuće tvari

Proizvedene su prema normi EN 1492-2.

NOSIVOST

Tablica nosivosti za beskonačne priveznice			 45° α <math><60^\circ</math>		 7° α <math><45^\circ</math>
Oznaka	WLL 1	WLL 0,8	WLL 1	WLL 2	WLL 1,4
boja	kg	kg	kg	kg	kg
IRS 10	1.000	800	1.000	2.000	1.400
IRS 20	2.000	1.600	2.000	4.000	2.800
IRS 30	3.000	2.400	3.000	6.000	4.200
IRS 40	4.000	3.200	4.000	8.000	5.600
IRS 50	5.000	4.000	5.000	10.000	7.000
IRS 60	6.000	4.800	6.000	12.000	8.400
IRS 80	8.000	6.400	8.000	16.000	11.200
IRS 100	10.000	8.000	10.000	20.000	14.000
IRS 120	12.000	9.600	12.000	24.000	16.800
IRS 150	15.000	12.000	15.000	30.000	21.000
IRS 200	20.000	16.000	20.000	40.000	28.000
IRS 250	25.000	20.000	25.000	50.000	35.000
IRS 300	30.000	24.000	30.000	60.000	42.000
IRS 400	40.000	32.000	40.000	80.000	56.000
IRS 500	50.000	40.000	50.000	100.000	70.000

Standardne dužine 1, 2, 3, 4, 5, 6, 8 i 10m, za druge druge nosivosti i duljine nas kontaktirajte.